

# Thickness dependence of the electronic properties in V2O3 thin films

C. Grygiel, Ch. Simon, B. Mercey, W. Prellier, R. Fresard, P. Limelette

#### ▶ To cite this version:

C. Grygiel, Ch. Simon, B. Mercey, W. Prellier, R. Fresard, et al.. Thickness dependence of the electronic properties in V2O3 thin films. Applied Physics Letters, 2007, 91 (26), pp.262103. 10.1063/1.2824465. hal-01870065

## HAL Id: hal-01870065 https://univ-tours.hal.science/hal-01870065

Submitted on 7 Sep 2018

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

### Thickness dependence of the electronic properties in V<sub>2</sub>O<sub>3</sub> thin films

C. Grygiel, Ch. Simon, B. Mercey, W. Prellier, and R. Frésard Laboratoire CRISMAT, UMR 6508 CNRS-ENSICAEN, 6, Boulevard du Maréchal Juin, 14050 Caen Cedex, France

#### P. Limelette

Laboratoire LEMA, CNRS-CEA UMR 6157, Université F. Rabelais, Parc de Grandmont, 37200 Tours, France

(Received 9 July 2007; accepted 21 November 2007; published online 26 December 2007)

High quality vanadium sesquioxide V<sub>2</sub>O<sub>3</sub> films (170–1100 Å) were grown using the pulsed laser deposition technique on (0001)-oriented sapphire substrates, and the effects of film thickness on the lattice strain and electronic properties were examined. X-ray diffraction indicates that there is an in-plane compressive lattice parameter (a), close to -3.5% with respect to the substrate and an out-of-plane tensile lattice parameter (c). The thin film samples display metallic character between 2 and 300 K, and no metal-to-insulator transition is observed. At low temperature, the V<sub>2</sub>O<sub>3</sub> films behave as a strongly correlated metal, and the resistivity  $(\rho)$  follows the equation  $\rho = \rho_0 + AT^2$ , where A is the transport coefficient in a Fermi liquid. Typical values of A have been calculated to be  $0.14~\mu\Omega$  cm K<sup>-2</sup>, which is in agreement with the coefficient reported for  $V_2O_3$  single crystals under high pressure. Moreover, a strong temperature dependence of the Hall resistance confirms the electronic correlations of these V<sub>2</sub>O<sub>3</sub> thin film samples. © 2007 American Institute of Physics. [DOI: 10.1063/1.2824465]

First discovered by Foex in 1946, vanadium sesquioxide V<sub>2</sub>O<sub>3</sub> has received a great deal of attention, both by theoreticians as well as experimentalists. Indeed, it has been recognized previously that a pressure-induced metal-toinsulator transition (MIT) for V<sub>2</sub>O<sub>3</sub> is driven by electron correlation,<sup>2</sup> establishing V<sub>2</sub>O<sub>3</sub> as a prototypical strongly correlated electron system. As a result, numerous studies on the effect of composition or external parameters on the transport properties of V<sub>2</sub>O<sub>3</sub> have been reported.<sup>3-5</sup> Particular attention has also been paid to the phase transitions of V<sub>2</sub>O<sub>3</sub>: in the pressure-temperature plane, two phase transitions are reported, either when applying a hydrostatic pressure or a chemical pressure [see, for example,  $(V_{1-x}M_x)_2O_3$  with M=Cr, Ti, ...].<sup>3,4</sup> For example, a system that is close to all phase boundaries is  $(V_{0.985}Cr_{0.015})_2O_3$  at 200 K.<sup>6</sup> When the temperature is decreased, this paramagnetic metal undergoes a first order phase transition from a corundum structure with rhombohedral symmetry  $(R\bar{3}c)$  space group, with a=4.951 Å and c=14.003 Å) to an antiferromagnetic insulator with monoclinic structure (I2/a). When the temperature or the Cr content is increased, a paramagnetic metalto-paramagnetic insulator transition takes place. While the former transition bears strong similarities with many usual magnetic transitions, the latter one corresponds to the famous Mott transition. Qualitatively, this Mott transition is well described by the Hubbard model: increasing the Cr content results in increasing the ratio U/W (U being the strength of the Coulomb interaction and W the bandwidth), in which case the quasiparticle residue decreases and eventually vanishes at the MIT.8 Furthermore, when considering the optical conductivity, the optical weight at low energy is transferred to energies of order U. When the system is close to the Mott point, thermal fluctuations destabilize the coherence of the Fermi liquid (FL), and an increase in temperature results into a MIT. 10-12 Several orbitals are involved at the Fermi energy

and, however, a quantitative description of V<sub>2</sub>O<sub>3</sub> needs to build on a more involved theory, such as the one pioneered by Held et al. 13

Despite the extensive studies on polycrystalline powder and single crystal V<sub>2</sub>O<sub>3</sub> samples, <sup>14-17</sup> there have been few reports on thin film samples. Schuler et al. addressed the influence of the synthesis conditions upon the classical metal-to-insulator transition and the growth modes of the films. 18 The relation between the transition temperatures and the lattice parameters have also been reported. 19-21 There is little knowledge, however, on the thickness dependence of the properties of the V<sub>2</sub>O<sub>3</sub> thin films. In addition, phase transitions can have exciting applications in emerging nanoelectronic devices such as bolometers or sensors.<sup>22</sup> Moreover, it is required for such applications to have V<sub>2</sub>O<sub>3</sub> thin films, the properties of which are clearly mastered up to a low thickness.

In this letter, we examine a series of epitaxial V<sub>2</sub>O<sub>3</sub> thin films, including their lattice parameters, roughness, and Hall resistance, in order to investigate their transport properties as a function of thickness. Samples of V<sub>2</sub>O<sub>3</sub> thin films, of which the thickness ranged from 170 to 1100 Å, were grown on (0001)-oriented Al<sub>2</sub>O<sub>3</sub> substrates (rhombohedral with the parameters a=4.758 Å and c=12.991 Å) from a  $V_2O_5$  target by the pulsed laser deposition technique. 19 The substrate heater was kept at a constant temperature ranging from 600 to 650 °C. A background of argon pressure around 0.02 mbar was applied inside the chamber. At the end of the deposition, the film was cooled down to room temperature at a rate of 10 K min<sup>-1</sup> under a 0.02 mbar argon pressure. The film thickness was determined, to an uncertainty below two V<sub>2</sub>O<sub>3</sub> unit cells, by a mechanical stylus measuring system (Dektak <sup>3</sup>ST). The structure of the films was examined by x-ray diffraction (XRD) (with the  $Cu K\alpha_1$  radiation,  $\lambda = 1.54056$  Å) using a Seifert 3000P diffractometer for the out-of-plane measurements and a Philips X'Pert for the inplane measurements. In-plane a lattice parameters were ex-

a) Electronic mail: prellier@ensicaen.fr.




FIG. 1. (Color online) Thickness dependence of the  $\boldsymbol{a}$  and  $\boldsymbol{c}$  lattice parameters.

tracted from (104), (116), and (113) asymmetric reflections. The resistivities of the samples were measured in four-probe configuration using a physical property measurement system. For Hall effect measurements, a Van der Pauw configuration was used. For each temperature value, the transverse resistance is measured with an applied magnetic field (H) varying from -7 up to +7 T. The Hall resistance  $R_H$  is calculated from the transverse resistance ( $R_{xy}$ ) using the formula  $R_H = (tR_{xy})/H$ .

As it is known that the nonstoichiometry can drastically influence the electric properties of V<sub>2</sub>O<sub>3</sub>, <sup>15</sup> an x-ray photoelectron spectroscopy study was carried out. It shows that the oxidation state of vanadium can be estimated around +3, confirming that the films stoichiometry is close to  $V_2O_3$ . Here  $\Theta$ -2 $\Theta$  scan XRD measurements reveal that only the peaks corresponding to the 00l reflections (where l=6, 12, ...) are present, which indicates that the c axis of the films is perpendicular to the plane of the substrate. Moreover,  $\Phi$  scans, recorded around the (104) reflection, show three peaks separated by 120° from each other, indicating that the films have a threefold symmetry and are grown epitaxialy, with respect to the substrate. These results are in agreement with the rhombohedral symmetry observed in the bulk  $V_2O_3$ . This symmetry and the  $R\bar{3}c$  space group are further confirmed by electron diffraction pattern analyses. The high quality of the films was also attested by the low value of the rocking curve close to (0.20°) measured around the (006) reflection of the film.

Figure 1 displays the evolution of the lattice parameters (c) and (a), characteristic of the  $R\overline{3}c$  structure, as a function of the thickness t. The out-of-plane lattice parameter (c) is slightly larger than the bulk values by  $(0.45\pm0.1)\%$ , while the in-plane (a) is smaller by  $(-0.55\pm0.1)\%$ , confirming a biaxial compression in the (ab) plane, estimated to be  $(-3.5\pm0.5)\%$  with respect to the substrate [the stress values are calculated from the mean values (c) and (a) obtained from the thickness dependence in Fig. 1]. This suggests an




FIG. 2. (Color online) Temperature dependence of the longitudinal resistivity of several  $V_2O_3$  thin films.

anisotropic strain similar to previous reports.<sup>20</sup> Surprisingly, the lattice parameters are almost independent of t, indicating that the films are fully strained in the whole thickness range. The surface morphology was also studied by atomic force microscopy (AFM) with a scan area of  $3 \times 3 \mu m^2$ . Topography of the V<sub>2</sub>O<sub>3</sub> samples reveals that the roughness increases when the thickness increases. For example, a typical surface roughness (rms) of 4.5 Å was observed for the thinnest film (170 Å), while a thicker sample (700 Å) has a rms value of 11 Å. This may indicate that the growth mode is mixed: a layer by layer (two-dimensional mode) on the (ab) plane at the initial step of the growth and an island coalescence (three-dimensional mode) along the c axis when the thickness increases. To summarize, the structural and microstructural analyses confirm that the films crystallize in the  $R\overline{3}c$ structure, as in bulk, despite a large in-plane compressive strain.

The longitudinal resistivity ( $\rho$ ) of  $V_2O_3$  films is plotted in Fig. 2 as a function of temperature. In contrast to bulk samples, none of the investigated films exhibit a strong temperature-dependent resistivity. This is especially valid for t > 220 Å, in which case the resistivity increases continuously with temperature as in a metal. Nevertheless, some hysteresis is observed, though strongly suppressed with respect to the bulk. The relative positions of the resistivity curves are not significant of a thickness dependence. It mostly results from the residual resistivity  $\rho_0$ , which depends on extrinsic factors such as scattering at the grain boundaries. As can be seen in Table I, the values of  $\rho_0$  vary even under similar growth conditions. Thus, we can conjecture that the above found stress in the (ab) plane results into a larger bandwidth and hinders the paramagnetic metal-toantiferromagnetic insulator transition. In contrast, for thinner films (t < 220 Å), the films are metallic with a weak increase of the resistivity near 150 K. Its origin might be a reminder of the structural transition.

As shown in Fig. 3, resistivity data for all films follow a law in  $\rho = \rho_0 + AT^2$  in the temperature range from 2 K up to a

TABLE I. Thickness t, residual resistivity  $\rho_0$ , Fermi liquid transport coefficient A, temperature  $T_d$ , carriers number n, and Hall mobility  $\mu_H$  for three films.

t (Å)	$ ho_0~({ m m}\Omega~{ m cm})$	$A~(10^{-5}~\mathrm{m}\Omega~\mathrm{cm}~\mathrm{K}^{-2})$	$T_d$ (K)	$n_{300 \ K} \ (\text{cm}^{-3})$	$\mu_{H(300 \text{ K})}$ [cm <sup>2</sup> (V s) <sup>-1</sup> ]
1100	0.24	19.6	18.7	$4.5 \pm 0.210^{22}$	0.16±0.05
380	0.27	14.0	17.5	$4.4 \pm 0.410^{22}$	$0.15 \pm 0.06$
260	0.19	10.2	15.8	$4.9 \pm 0.510^{22}$	$0.21 \pm 0.10$




FIG. 3. (Color online) Resistivity vs  $T^2$  in the low temperature region. The  $T_d$  temperature is also indicated.

characteristic temperature  $T_d$ . Here,  $\rho_0$  represents the (film dependent) residual resistivity and A the transport coefficient in a Fermi liquid. This behavior, which differs from simple metals that exhibit  $T^3$  or  $T^5$  behavior, is seldom observed over such a temperature range, except for a few strongly correlated electron system, such as Ca<sub>3</sub>Co<sub>4</sub>O<sub>9</sub>. <sup>23</sup> Table I summarizes the values  $\rho_0$ , A, and  $T_d$  for a series of films. The average value of A is close to 0.14  $\mu\Omega$  cm K<sup>-2</sup> across the whole thickness range, indicating that the A coefficient is not significantly thickness dependent. Moreover, it should be noted that such values are similar to those measured for single crystal V<sub>2</sub>O<sub>3</sub> samples subjected to high pressures (26-52 kbars). The high A values involve the existence of strong electronic correlations in our metallic thin films. The product  $A(T_d)^2/a$  is about two orders of magnitude lower than  $h/e^2$ , indicating that the FL behavior does not extend up to the effective Fermi temperature. Instead, an additional scattering channel opens up at  $T > T_d$ , which might be provided by spin fluctuations. To better quantify the temperature range where this scattering channel is relevant, we performed Hall effect measurements in the temperature range of 2-300 K. Figure 4 shows the resulting Hall resistance  $(R_H)$ for a series of films. The positive slope of the Hall resistance implies holelike charge carriers, as inferred by McWhan and Remeika.<sup>14</sup> Moreover, while the Hall resistance would be nearly temperature independent in a regular metal, here, it exhibits a strong temperature dependence, especially for T < 200 K. In particular, the strain involved in our films has little influence on the location of the maximum of  $R_H$ , as it is located at a temperature very close to the one reported for metallic bulk samples.<sup>24</sup> Nevertheless, this temperature slightly increases as the thickness decreases. A similar result has been observed in the aforementioned single crystals with an increase in pressure, indicating that the decrease of the thickness is consistent with an increase of the pressure. At room temperature, in the temperature-independent regime, the values of the carrier number (n) and Hall mobility  $(\mu_H)$ can also be extracted from the Hall resistance value (see Table I). For the thicker film (1100 Å), they are calculated to be  $n=4.5\pm0.210^{22}$  cm<sup>-3</sup> and  $\mu_H=0.16\pm0.05$  cm<sup>2</sup> V<sup>-1</sup> s<sup>-1</sup>, which are consistent with the ones observed in V<sub>2</sub>O<sub>3</sub> single crystals.  $^{14}$  Note that  $R_H$  looses its temperature dependence above ~200 K, which indicates that above this temperature, the correlation length of the fluctuations that scatter the electrons becomes of the order of the lattice parameter. Consequently, in this regime, the resistivity is expected to be T linear, which is indeed observed for most of the films.

In summary, high quality epitaxial V<sub>2</sub>O<sub>3</sub> thin films were grown, with thickness ranging from 170 to 1100 Å by




FIG. 4. (Color online) Temperature dependence of the Hall resistance of several  $V_2O_3$  thin films.

pulsed laser deposition on sapphire substrate (0001-Al<sub>2</sub>O<sub>3</sub>). Using multiple of characterization techniques, we confirm that the films have the same rhombohedral structure ( $R\bar{3}c$  space group) as in the bulk despite the substrate-induced strains. The thickness dependence of the electronic properties shows the suppression of the classical metal-to-insulator transition with a metal-like behavior. At low temperature, the dependence of the resistivity as a function of  $T^2$  was measured to be that of a strong correlated metal, and it was confirmed by temperature dependence of the Hall resistance.

We thank D. Grebille and A. Pautrat for fruitful discussions. J. F. Hamet and Y. Thimont are also acknowledged for the AFM measurements. This work is carried out in the frame of the STREP CoMePhS (NMP3-CT-2005-517039) supported by the European community and by the CNRS, France.

<sup>1</sup>M. Foex, C. R. Acad. Sci. III **223**, 1126 (1946).

<sup>2</sup>N. F. Mott, Proc. Phys. Soc., London, Sect. A **62**, 416 (1949).

<sup>3</sup>D. B. McWhan, A. Menth, J. P. Remeika, W. F. Brinkman, and T. M. Rice, Phys. Rev. B **7**, 1920 (1973).

<sup>4</sup>M. Yethiraj, J. Solid State Chem. **88**, 53 (1990).

<sup>5</sup>P. Limelette, A. Georges, D. Jérome, P. Wzietek, P. Metcalf, and J. M. Honig, Science **302**, 89 (2003).

<sup>6</sup>H. Kuwamoto, J. M. Honig, and J. Appel, Phys. Rev. B **22**, 2626 (1980).

<sup>7</sup>P. Dernier and M. Marezio, Phys. Rev. B **2**, 3771 (1970).

<sup>8</sup>W. F. Brinckman and T. M. Rice, Phys. Rev. B **2**, 4302 (1970).

<sup>9</sup>G. A. Thomas, D. H. Rapkine, S. A. Carter, A. J. Millis, T. F. Rosenbaum, P. Metcalf, and J. M. Honig, Phys. Rev. Lett. 73, 1529 (1994).

<sup>10</sup>J. Spałek, A. Datta, and J. M. Honig, Phys. Rev. Lett. **59**, 728 (1987).

<sup>11</sup>A. Georges, G. Kotliar, W. Krauth, and M. J. Rozenberg, Rev. Mod. Phys. 68, 13 (1996).

<sup>12</sup>R. Frésard and G. Kotliar, Phys. Rev. B **56**, 12 909 (1997).

<sup>13</sup>K. Held, G. Keller, V. Eyert, D. Vollhardt, and V. I. Anisimov, Phys. Rev. Lett. **86**, 5345 (2001).

<sup>14</sup>D. B. McWhan and J. P. Remeika, Phys. Rev. B **2**, 3734 (1970).

<sup>15</sup>Y. Ueda, K. Kosuge, and S. Kachi, J. Solid State Chem. **31**, 171 (1980).

<sup>16</sup>S. A. Shivashankar and J. M. Honig, Phys. Rev. B **28**, 5695 (1983).

<sup>17</sup>D. B. McWhan and T. M. Rice, Phys. Rev. Lett. **22**, 887 (1969).

<sup>18</sup>H. Schuler, S. Klimm, G. Weissmann, C. Renner, and S. Horn, Thin Solid Films 299, 119 (1997).

<sup>19</sup>S. Autier-Laurent, B. Mercey, D. Chippaux, P. Limelette, and Ch. Simon, Phys. Rev. B 74, 195109 (2006).

<sup>20</sup>S. Yonezawa, Y. Muraoka, Y. Ueda, and Z. Hiroi, Solid State Commun. 129, 245 (2004).

<sup>21</sup>Q. Luo, Q. Guo, and E. G. Wang, Appl. Phys. Lett. **84**, 2337 (2004).

<sup>22</sup>L. Mechin, J.-M. Routoure, B. Guillet, F. Yang, S. Flament, D. Robbes, and R. A. Chakalov, Appl. Phys. Lett. 87, 204103 (2005).

<sup>23</sup>P. Limelette, V. Hardy, P. Auban-Senzier, D. Jérome, D. Flahaut, S. Hébert, R. Frésard, Ch. Simon, J. Noudem, and A. Maignan, Phys. Rev. B 71, 233108 (2005).

<sup>24</sup>S. A. Carter, T. F. Rosenbaum, P. Metcalf, J. M. Honig, and J. Spałek, Phys. Rev. B 48, 16841 (1993).